

OUT BOARD ENGINE OIL

DESCRIPTION

OUTBOARD ENGINE OIL is an ashless lubricating oil formulated to meet the critical requirements of high performance, water or air cooled two-stroke gasoline engines.

APPLICATIONS

OUTBOARD ENGINE OIL is recommended for high output two-stroke water or air cooled gasoline engines. It should be added with the fuel in the ratio as recommended by the equipment manufacturer.

BENEFITS

- Controls combustion chamber and spark plug deposits build-up.
- Excellent miscibility with gasoline.
- Keeps pistons, rings, plugs and exhaust ports clean.
- Resistance to low temperature gel formation.
- Protects against rust by fresh or salt water.

PERFORMANCE LEVEL

NMMA TC-W3 R

PRODUCT TYPICAL CHARACTERISTICS

PROPERTIES		UNITS	VALUE	TEST METHOD
Grade		-	-	-
Specific Gravity	@ 15°C	-	0.8785	ASTM D-1298
Viscosity	@ 40°C	mm ² /s	Report	ASTM D-445
	@ 100°C	mm ² /s	7.30	ASTM D-445
Flash Point	PMCC	°C	72	ASTM D-93
Pour Point		°C	-30	ASTM D-97
Color		-	Green	VISUAL