

SUPREME 2T ENGINE OIL

DESCRIPTION

SUPREME 2T ENGINE OIL is a semi-synthetic two-cycle oil formulated from a special blend of mineral and synthetic oil and low-ash additive package to release maximum power with minimum drag.

APPLICATIONS

SUPREME 2T ENGINE OIL is recommended for high performance, motorcycles, especially for road use. It is also recommended for smaller engine fitted in scooters, lawn mowers and other small equipment. It should be added with gasoline in the ratio recommended by the equipment manufacturer.

BENEFITS

- Superior combustion characteristics of the special blend of Semi-Synthetic and highly refined mineral oils and additives, significantly reduces visible smoke in exhaust emission.
- Controls combustion chamber and spark plug deposit build-up.
- Excellent miscibility with gasoline.
- Keeps pistons, rings, plugs and exhaust ports clean.

PERFORMANCE LEVEL

JASO.....FD
 API.....TC
 ISO.....L-EGD

PRODUCT TYPICAL CHARACTERISTICS

PROPERTIES		UNITS	VALUE	TEST METHOD
Grade		-	-	-
Specific Gravity	@ 15°C	-	0.8720	ASTM D-1298
Viscosity	@ 40°C	mm ² /s	-	ASTM D-445
	@ 100°C	mm ² /s	9.0	ASTM D-445
Viscosity Index		-	-	ASTM D-2270
Flash Point	PMCC	°C	70	ASTM D-93
Pour Point		°C	-30	ASTM D-97
Color		-	2.0	ASTM D-1500