

# AUTOMATIC TRANSMISSION FLUID DII

## DESCRIPTION

AUTOMATIC TRANSMISSION FLUID DII is formulated from special high quality solvent refined mineral base oil combined with special additives. It serves as a power transmission fluid in the torque converter, hydraulic fluid in the control and servo systems, as a lubricant for bearing and gears and as a friction-controlling medium for bands and clutches.

## APPLICATIONS

AUTOMATIC TRANSMISSION FLUID DII is formulated to meet the requirements of passenger car and light truck automatic transmissions, power steering and other hydraulic systems.

## BENEFITS

- Effective frictional characteristics for smooth shifting.
- Excellent fluidity at low temperature application.
- Good protection against wear.
- Reduced foaming and fluid loss under severe service conditions.
- Protection against high-temperature deposits in heavy duty service.

## PERFORMANCE LEVEL

Dexron II, Dexron.  
Type A suffix A.  
Allison C4.

## PRODUCT TYPICAL CHARACTERISTICS

PROPERTIES		UNITS	VALUE	TEST METHOD
Grade		-	ATF D-II	-
Specific Gravity	@ 15°C	-	0.8525	ASTM D-1298
Viscosity	@ 40°C	mm <sup>2</sup> /s	33.70	ASTM D-445
	@ 100°C	mm <sup>2</sup> /s	7.300	ASTM D-445
Viscosity Index		-	190	ASTM D-2270
Flash Point	COC	°C	170	ASTM D-92
Pour Point		°C	-48	ASTM D-97
Color		-	Red	VISUAL