

# GENERAL PURPOSE OIL

## 32, 68, 100, 150

### DESCRIPTION

GENERAL PURPOSE OIL is a high quality solvent-refined paraffinic oil containing no additives and possess inherent oxidation stability.

### APPLICATIONS

GENERAL PURPOSE OIL is suitable for bearing and gear lubrication systems where the operating conditions are not severe. It is recommended for use in re-circulating and other closed oil systems. Also suitable for many industrial hydraulic applications where non additive oils are required.

### BENEFITS

- Inherent Oxidation Stability.
- Low Volatility.

### PRODUCT TYPICAL CHARACTERISTICS

PROPERTIES		UNITS	VALUE				TEST METHOD
Grade		-	68	100	150	220	-
Specific Gravity	@ 15°C	-	0.8650	0.8730	0.8850	0.8920	ASTM D-1298
Viscosity	@ 40°C	mm <sup>2</sup> /s	31.00	68.00	95.00	150.0	ASTM D-445
	@ 100°C	mm <sup>2</sup> /s	5.23	8.60	10.75	14.60	ASTM D-445
Viscosity Index		-	98	96	96	96	ASTM D-2270
Flash Point	COC	°C	214	230	240	250	ASTM D-92
Pour Point		°C	-15	-12	-9	-12	ASTM D-97
Color		-	0.5	1.0	1.5	2.0	ASTM D-1500